



VF X SERIES

Premium Freezer Range

Display / Top Mount

The new X series takes the popular VF premium, energy efficient freezers to a new level with a modern frameless glass door, redesigned louvre, and patented easy to install shelf clip and support system.

- Options**
- LED sign panel
 - Barrel key door locks
 - LED Lighting (option on solid door, std on glass door)
 - Extra shelf layer
 - Solid doors
 - Condenser filter



SKOPE Cyclone™ refrigeration system

Standard door locks

Available with glass or solid doors

Ergonomically designed, brushed aluminium door handles

Ducted balanced air flow system for consistent product temperatures

Optional illuminated LED T8 tube sign panel

Controller / Display

- Electronic controller maintains precise temperature control
- Stabilised temperature display indicates actual product temperature
 - Manual light switch
 - Door open alarm
 - High ambient alarm

Available in white, black and stainless steel (additional cost for S/S)

New Features


- Removable louvre for quick and easy maintenance
- Modern triple glazed frameless glass door
- High efficiency, long-life LED strip lights in cabinet
- Patented easy to install shelf clip and numbered shelf support strip, reduces set up time and enables finer adjustments




Specifications

VF X Series


Display / Top Mount Freezer




Integral top view




Integral front elevation




Integral top view




Integral front elevation




Integral top view



Integral front elevation



Integral top view



Integral front elevation

VF650X - GLASS/SOLID DOOR

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	Gross Volume 610 litres Total Shelf Area 1.46m ² (excluding floor) Floor Area 0.55m ²
VF650X	207	Integral	Freezer	
VF650Xr	192	Remote	Freezer	
	External (mm)	Internal (mm)		
Height	2200	1570		
Width	740	640		
Depth**	745	554		

- 24.27 MEPS (kWh/24h/m²)
- Remote refrigeration duty 820 Watts at -30°C SST
- -18°C to -21°C in 40°C ambient



VF650X
1 DOOR

VF1000X - GLASS/SOLID DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	Gross Volume 980 litres Total Shelf Area 2.34m ² (excluding floor) Floor Area 0.84m ²
VF1000X	292	Integral	Freezer	
VF1000Xr	267	Remote	Freezer	
	External (mm)	Internal (mm)		
Height*	2210	1570		
Width	1130	1030		
Depth**	745	554		

- 25.73 MEPS (kWh/24h/m²)
- Remote refrigeration duty 1280 Watts at -30°C SST
- -18°C to -21°C in 40°C ambient



VF1000X
2 DOOR

VF1300X - GLASS/SOLID DOORS (Wide)

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	Gross Volume 1310 litres Total Shelf Area 3.11m ² (excluding floor) Floor Area 1.05m ²
VF1300X	347	Integral	Freezer	
VF1300Xr	322	Remote	Freezer	
	External (mm)	Internal (mm)		
Height*	2210	1570		
Width	1480	1380		
Depth**	745	554		

- 22.36 MEPS (kWh/24h/m²)
- Remote refrigeration duty 1500 Watts at -30°C SST
- -18°C to -21°C in 40°C ambient



VF1300X
2 DOOR

VF1500X - GLASS/SOLID DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	Gross Volume 1500 litres Total Shelf Area 3.67m ² (excluding floor) Floor Area 1.27m ²
VF1500X	372	Integral	Freezer	
VF1500Xr	342	Remote	Freezer	
	External (mm)	Internal (mm)		
Height	2200	1570		
Width	1705	1605		
Depth**	745	554		

- 32.10 MEPS (kWh/24h/m²)
- Remote refrigeration duty 1900 Watts at -30°C SST
- -18°C to -21°C in 40°C ambient



VF1500X
3 DOOR

*Height includes freezer unit lid ** Depth includes removable door handle and lock bracket